

NATIONAL INSTITUTE FOR FUSION SCIENCE

Reduction of Turbulence by Sheared Toroidal Flow
on a Flux Surface

T. Ohkawa

(Received - Feb. 5, 1997)

NIFS-484

Feb. 1997

RESEARCH REPORT NIFS Series

This report was prepared as a preprint of work performed as a collaboration research of the National Institute for Fusion Science (NIFS) of Japan. This document is intended for information only and for future publication in a journal after some rearrangements of its contents.

Inquiries about copyright and reproduction should be addressed to the Research Information Center, National Institute for Fusion Science, Nagoya 464-01, Japan.

NAGOYA, JAPAN

Reduction of Turbulence by Sheared Toroidal Flow on a Flux Surface

Tihiro Ohkawa

National Institute for Fusion Science

and

Department of Physics, University of California at San Diego

Abstract

When the tokamak plasma is heated by neutral beam injection, the pressure of the high energy ions is generally not uniform on a flux surface. The distribution depends on the injection geometry. The response of the electrons, described by Ohm's law results in the sheared toroidal rotation of the plasma on a flux surface. Because the turbulence has long correlation lengths parallel to the magnetic field, the rotational shear on a flux surface is more effective for suppressing the turbulences with short radial correlation length than the rotational shear across the flux surface.

Keywords: sheared toroidal flow, turbulence suppression, energetic ions, anomalous transport, confinement improvement, negative magnetic shear

1. Introduction

The improved confinement regimes of tokamak plasma with negative shear¹⁾ are under intense theoretical study. The reduction of the turbulence²⁾ by shear of plasma flow across a flux surface have been proposed as the underlying cause of the improvement. The turbulence with a significant radial correlation length will be "washed away" by the flow shear. On the other hand, the turbulence with very short radial correlation length are difficult to suppress by this mechanism. Since the orbits of the electrons are much smaller than those of the ions, one might speculate that the electron heat transport is due to the turbulence of short radial correlation length and that is why only the ion heat transport is reduced in the experiments.

The recent experimental results³⁾ from JT-60U have shown that the electron heat transport is reduced as well as the ion heat transport. It suggests that there may be a different mechanism at work which reduces the electron heat transport.

Because the correlation along the magnetic field is much better than across the magnetic field, the turbulence is expected to have elongated shapes parallel to the magnetic field. If there is a shear in the toroidal flow of the plasma on a flux surface, the turbulence will quickly decorrelate independent of the radial correlation length. In plasma with the temperature and the density uniform on a flux surface, Ohm's law dictates there is no shear in the toroidal flow. However, when the plasma contains a significant amount of high energy ions from the neutral beam injection, the situation changes. The magnetic force must support the force exerted by the high energy ions for the equilibrium. The extra magnetic force in Ohm's law results in a sheared toroidal flow on a flux surface.

If the sheared flow reduces the electron heat transport, the electron temperature increases. As a result the beam slow down time lengthens and the high energy ion component increases. A positive feed back loop is established and the electron temperature reaches a high value until the beam slow down is mainly due to the collisions with the ions. It seems that this mechanism leads to a bifurcation, either the electron temperature stays low or reaches a high value.

In the following we discuss Ohm's law, high energy ion component, toroidal rotation and the effect on the turbulence.

2. Ohm's law

The electron heat conduction along the magnetic field lines is rapid and also the electron collision frequency is much higher than that of the ions. Therefore we assume that the electron temperature is uniform on a flux surface and the electron pressure is isotropic. The force balance equation of the electron fluid becomes

$$\vec{E} + \vec{v} \times \vec{B} = \frac{1}{en}(-\nabla p_e + \vec{j} \times \vec{B}) \quad (1)$$

Superficially the above equation looks like Ohm's law of the ordinary plasma. The effects of the high energy ion component are hidden in the magnetic force term $\vec{j} \times \vec{B}$ which must support the force exerted by the high energy ions as well as the thermal plasma pressure.

In the absence of the high energy ions, the equilibrium condition is given by

$$\vec{j} \times \vec{B} = \nabla p(\psi) \quad (2)$$

where p is the pressure and ψ is the flux function. The combination of eq.(1) and eq.(2) results in the well known relationship given by

$$\Omega \equiv \frac{v_\phi}{R} = \Phi'(\psi) + \frac{1}{en}(-p_e'(\psi) + p'(\psi)) \quad (3)$$

where ϕ is the toroidal angle, R is the major radius, Φ is the electrostatic potential and the prime denotes the derivative. It shows that the toroidal rotation is uniform on a flux surface. In obtaining eq.(3) it has been assumed that the poloidal rotation is suppressed by the neo-classical parallel viscosity.

3. High energy ions

When a neutral beam is injected into the plasma the beam ions slow down by colliding with the electrons until the energy decreases to the critical energy W_c , below which the beam ions scatter and slow down by colliding with the plasma ions. The critical energy is give by

$$W_c = 2^{3/2} (m_i / m_e)^{1/3} k_B T_e \quad (4)$$

The velocity spectrum f_b of the high energy ions⁴⁾ is approximately given by

$$f_b \simeq \frac{3n_b}{\ell n(1 + u_b^3 / u_c^3)} \frac{u^2}{u^3 + u_c^3} \quad (5)$$

where n_b is the ion density above the critical energy, u_b is the velocity at injection and u_c is the velocity at the critical energy. The energy density of the high energy ions p^* is given by

$$\begin{aligned} p^* &\equiv \frac{m_i}{2} \int_{u_c}^{u_b} f_b u^2 du \\ &= \frac{m_i}{4} \frac{3n_b}{\ell n(1 + u_b^3 / u_c^3)} \times \left[u_b^2 - u_c^2 \left(1 + \frac{1}{3} \ell n \left(\frac{4(u_b^2 - u_b u_c + u_c^2)}{(u_b + u_c)^3} \right) + \frac{2}{\sqrt{3}} \left(\tan^{-1} \frac{2u_b - u_c}{\sqrt{3}u_c} - \frac{\pi}{6} \right) \right) \right] \\ &\simeq \frac{m_i}{4} \frac{u_b^2 n_b}{\ell n(u_b / u_c)} \quad (u_b \gg u_c) \end{aligned} \quad (6)$$

The density n_b is determined by the injection current I_b into the volume V . We obtain

$$\begin{aligned} n_b &= \frac{I_b}{Ve v_{ie}} \\ &\simeq 0.8 I \times 10^{30} \frac{I_b}{V n} \left(\frac{k_B T_e}{e} \right)^{3/2} \end{aligned} \quad (7)$$

where v_{ie} is the reciprocal of the slow down time.

Since the collisions with electrons do not result in the pitch angle scattering, the spatial and velocity space distribution of the high energy ions are determined by the injection geometry. We consider two extremes, the perpendicular and the tangential injection.

The perpendicular injection puts the beam ions on the trapped orbits. The spatial distribution of the ions is weighted on the outboard side. To the first order of the inverse aspect ratio ϵ , the distribution of the perpendicular pressure p_\perp can be approximated by

$$p_{\perp} \simeq 2p^* \frac{R - R_I}{R_2 - R_I} \quad (8)$$

where R_2 and R_I are the maximum and the minimum radius of the flux surface .

When the injection is tangential; co, counter or balanced, the centrifugal force F_C must be supported. It is given by

$$F_c = \frac{2p^*}{R} \quad (9)$$

In term of the equivalent pressure p_c representing the centrifugal force, we obtain

$$p_c = 4p^* \frac{R - R_I}{R_2 - R_I} \quad (10)$$

Another way of looking at it is that the beam equilibrium is shifted radially outward relative to the flux surface. By comparing eq.(8) and eq.(10) one can see the effect of the centrifugal force is smaller by ϵ .

Although the generalized Grad-Shafranov equation⁵⁾ with anisotropic pressure and rotation is available, here we parameterize the contribution from the high energy ions as an additional pressure to be supported by the magnetic force. We assume that the contribution p_I of the high energy ions to the total pressure is given by

$$p_I = 2\alpha p^*(\psi) \frac{R - R_I}{R_2 - R_I} \quad (11)$$

where α is a parameter. For the perpendicular injection α is closed to unity and for the tangential injection it is of the order of ϵ . If the injection is into the barely trapped orbits the distribution of the energetic ions is similar to the "sloshing ions" in the mirror device and α can be a negative value.

We write the ψ -component of the equilibrium equation

$$(\vec{j} \times \vec{B})_\psi = \nabla_\psi \bar{p}(\psi) + 2\alpha \frac{R-R_I}{R_2-R_I} \nabla_\psi p^*(\psi) \quad (12)$$

where a low β -value is assumed and $B^{-1} \nabla_\psi B$ term is neglected. The second term represents the force needed to support the high energy ions.

4. Toroidal rotation

We calculate the toroidal rotation from Ohm's law using the pressure of the high energy ions estimated in the previous section. The component parallel to the magnetic field of Ohm's law yields

$$\Phi = \bar{\Phi}(\psi) + \frac{k_B T_e(\psi)}{e} \ell n\left(\frac{n}{\bar{n}(\psi)}\right) \quad (13)$$

where the bar indicates the values averaged over the flux surface. By using eq.(12), we obtain

$$\Omega = \bar{\Phi}' + \frac{k_B T_e'}{e} \left\{ \ell n\left(\frac{n}{\bar{n}}\right) - I \right\} - \frac{k_B T_e}{e} \frac{\bar{n}'}{\bar{n}} + \frac{1}{e\bar{n}} \left(\bar{p}' + 2\alpha \frac{R-R_I}{R_2-R_I} p^{*'} \right) \quad (14)$$

The high energy ions may contribute to the pressure significantly because of their energy but contribute very little to the density. Consequently we may neglect the density nonuniformity on the flux surface and obtain

$$\Omega = \bar{\Phi}' + \frac{1}{e\bar{n}} \left(\bar{p}' - p_e' + 2\alpha \frac{R-R_I}{R_2-R_I} p^{*'} \right) \quad (15)$$

The modulated part of the rotation frequency Ω^* is given by

$$\Omega^* = \frac{2\alpha}{e\bar{n}} \frac{R-R_I}{R_2-R_I} p^{*'} \quad (16)$$

5. Reduction of turbulence

The turbulent electrostatic potential $\tilde{\Phi}$ may be expanded in Fourier components

$$\tilde{\Phi}(r, \theta, \phi) = \sum_{M, N} \Phi_{N, M}(r) \exp(iN\phi - iM\theta - i\omega t) \quad (17)$$

where r is the minor radius, θ is the poloidal angle, N and M are the toroidal and the poloidal mode numbers and ω is the frequency. The plasma is assumed to have a circular cross section and the cylindrical coordinates are used.

If there is toroidal rotation $\Omega[r, \theta]$, the Doppler shifted phase difference $\Delta\varphi$ between the points (r_2, θ_2) and (r_1, θ_1) increases with time as

$$\Delta\varphi = (\Omega(r_2, \theta_2) - \Omega(r_1, \theta_1))Nt \quad (18)$$

The rotation has the uniform part $\bar{\Omega}$ and the modulated part Ω_I

$$\Omega = \bar{\Omega}(r) + \Omega_I \cos \theta \quad (19)$$

The phase shift between r_2 and r_1 is mainly caused by the derivative of the first term whereas the second term causes the phase shift between different poloidal positions.

The turbulence is expected to have very small parallel wave numbers compared to the perpendicular wave numbers. For very small parallel wave number, the mode numbers satisfy

$$N \sim Mq^{-1} \quad (20)$$

where q is the safety factor. For these modes the correlation length extends along the magnetic field line from $\theta = 0$ to $\theta = \pi$. The phase shift across the correlation lengths is given by

$$\Delta\varphi \simeq \left(\frac{\bar{\Omega}\Delta r}{\lambda} + 2\Omega_I \right) Nt \quad (21)$$

where Δr is the radial correlation length and λ is the gradient length of the rotation.

The radial correlation length can be very small. For example, if Δr is of the order of the ion gyroradius or London length [collisionless skin depth], $\Delta r / \lambda$ may be $\sim 10^{-2}$. Hence Ω_1 can be much smaller than $\bar{\Omega}$ and yet effective in decorrelating the turbulence with small radial correlation length. In the limit of $\Delta r \rightarrow 0$, the phase shift becomes

$$\begin{aligned}\Delta\varphi &\simeq \frac{4\alpha p^* N t}{enRB_0\lambda} \\ &\simeq \left(\frac{p^*}{p_e}\right) 2\alpha\omega^* t\end{aligned}\tag{22}$$

where ω^* is the drift wave frequency without the gyroradius correction. The turbulence may be suppressed if the phase shift become large, $\Delta\varphi \sim 1$, during the correlation time or the reciprocal of the growth rate γ . The condition is given by

$$\gamma < \left(\frac{p^*}{p_e}\right) 2\alpha\omega^*\tag{23}$$

It shows that the turbulence may be suppressed when the pressures of the high energy ions becomes a significant fraction of the plasma pressure.

When the beam is injected into the plasma at a low electron temperature, the pressure of the high energy ions may not be sufficient to suppress the turbulence because the pressure is proportional to $3/2$ power of the electron temperature for a given plasma density. The turbulent transport of the electron heat continues and the electron temperature remains low. By either a separate electron heating or by increasing the beam power, the pressure of the high energy ions may reach the value sufficient to suppress the turbulence, The electron temperature rises because of the reduced transport. Consequently the pressure of the high energy ions rises further closing a positive feed back loop. Finally the critical energy becomes higher than injection energy and the pressure of the high energy ions becomes insensitive to the electron temperature. Also the beam ions cease to heat the electrons directly. There seem to exist two states, one at a low electron temperature with a poor electron heat confinement and the other at a high electron temperature with a good confinement.

6. Discussion

The recent experimental data of JT-60U is tantalizingly suggestive. At the final electron temperature at 9 keV and the beam energy of 90 keV the critical energy is above the injection energy. The beam ions scatter and slow down by colliding with the plasma ions. At the density of $3 \times 10^{19} \text{ m}^{-3}$, the pressure of the high energy ions is estimated to be several percent of the electron pressure. To estimate the value of α more detailed informations on the injection geometry is needed. The most direct test for the model is to measure the toroidal rotation velocity at both the inboard side and the outboard side. If the difference in the rotational frequency can be correlated with the improved electron heat confinement, the experimental support for the model is strong. The measured rotational velocity is in the range of 10^5 m/s . If the model is correct, the velocity difference between the outboard side and the inboard side of roughly 10^4 m/s is expected. Also there may be methods to enhance the effect such as a higher beam energy [500 keV] or a separate electron heating to test the model indirectly.

A question may arise why the negative shear is necessary for the improvement of the confinement. If the improvement is due to the effects described here, the high energy ion component is required. In the positive shear regimes these ions in the trapped orbits drift in the "bad" direction and are likely to cause "fish bone" type of the mhd activity. With the negative shear, the drift velocity of the shallowly trapped ions becomes in the "good" direction and the mhd activity may not occur. Thus the negative shear allows the presence of the energetic trapped ions without the deleterious mhd activities.

In this note we discussed the beam heated plasma. However, non-uniform ion pressure can be produced by r-f heating. The ICRF heating may create and maintain high energy trapped ion populations which resemble the high energy ion component produced by a neutral beam injection. If the model is confirmed by the experimental measurement, the design of future devices would be able to incorporate the injection geometry or an ion heating method to enhance the effect.

References

- [1] F.M. Levinton et al., *Phys. Rev. Lett.* **75**, 4412 (1995)
E.J. Strait et al., *Phys. Rev. Lett.* **75**, 4421 (1995)
- [2] H.Bigrari, P.H.Diamond and P.W Terry, *Phys. Fluid B* **2**, 1 (1990)
- [3] JT-60U Exp. Report No **40** JAERI (1996)
- [4] T. Ohkawa, *Nuclear Fusion* **10**, 185 (1970)
- [5] V.I. Ilgisonis, *Phys. Plasmas* **3**, 4577 (1996)

Recent Issues of NIFS Series

- NIFS-442 K. Toi, K.N. Sato, Y. Hamada, S. Ohdachi, H. Sakakita, A. Nishizawa, A. Ejiri, K. Narihara, H. Kuramoto, Y. Kawasumi, S. Kubo, T. Seki, K. Kitachi, J. Xu, K. Ida, K. Kawahata, I. Nomura, K. Adachi, R. Akiyama, A. Fujisawa, J. Fujita, N. Hiraki, S. Hidekuma, S. Hirokura, H. Idei, T. Ido, H. Iguchi, K. Iwasaki, M. Isobe, O. Kaneko, Y. Kano, M. Kojima, J. Koog, R. Kumazawa, T. Kuroda, J. Li, R. Liang, T. Minami, S. Morita, K. Ohkubo, Y. Oka, S. Okajima, M. Osakabe, Y. Sakawa, M. Sasao, K. Sato, T. Shimpō, T. Shoji, H. Sugai, T. Watari, I. Yamada and K. Yamauti,
Studies of Perturbative Plasma Transport, Ice Pellet Ablation and Sawtooth Phenomena in the JIPP T-IIU Tokamak; Sep. 1996 (IAEA-CN-64/A6-5)
- NIFS-443 Y. Todo, T. Sato and The Complexity Simulation Group,
Vlasov-MHD and Particle-MHD Simulations of the Toroidal Alfvén Eigenmode; Sep. 1996 (IAEA-CN-64/D2-3)
- NIFS-444 A. Fujisawa, S. Kubo, H. Iguchi, H. Idei, T. Minami, H. Sanuki, K. Itoh, S. Okamura, K. Matsuoka, K. Tanaka, S. Lee, M. Kojima, T.P. Crowley, Y. Hamada, M. Iwase, H. Nagasaki, H. Suzuki, N. Inoue, R. Akiyama, M. Osakabe, S. Morita, C. Takahashi, S. Muto, A. Ejiri, K. Ida, S. Nishimura, K. Narihara, I. Yamada, K. Toi, S. Ohdachi, T. Ozaki, A. Komori, K. Nishimura, S. Hidekuma, K. Ohkubo, D.A. Rasmussen, J.B. Wilgen, M. Murakami, T. Watari and M. Fujiwara,
An Experimental Study of Plasma Confinement and Heating Efficiency through the Potential Profile Measurements with a Heavy Ion Beam Probe in the Compact Helical System; Sep. 1996 (IAEA-CN-64/C1-5)
- NIFS-445 O. Motojima, N. Yanagi, S. Imagawa, K. Takahata, S. Yamada, A. Iwamoto, H. Chikaraishi, S. Kitagawa, R. Maekawa, S. Masuzaki, T. Mito, T. Morisaki, A. Nishimura, S. Sakakibara, S. Satoh, T. Satow, H. Tamura, S. Tanahashi, K. Watanabe, S. Yamaguchi, J. Yamamoto, M. Fujiwara and A. Iiyoshi,
Superconducting Magnet Design and Construction of LHD; Sep. 1996 (IAEA-CN-64/G2-4)
- NIFS-446 S. Murakami, N. Nakajima, S. Okamura, M. Okamoto and U. Gasparino,
Orbit Effects of Energetic Particles on the Reachable β -Value and the Radial Electric Field in NBI and ECR Heated Heliotron Plasmas; Sep. 1996 (IAEA-CN-64/CP -6) Sep. 1996
- NIFS-447 K. Yamazaki, A. Sagara, O. Motojima, M. Fujiwara, T. Amano, H. Chikaraishi, S. Imagawa, T. Muroga, N. Noda, N. Ohyabu, T. Satow, J.F. Wang, K.Y. Watanabe, J. Yamamoto, H. Yamanishi, A. Kohyama, H. Matsui, O. Mitarai, T. Noda, A.A. Shishkin, S. Tanaka and T. Terai
Design Assessment of Heliotron Reactor; Sep. 1996 (IAEA-CN-64/G1-5)
- NIFS-448 M. Ozaki, T. Sato and the Complexity Simulation Group,
Interactions of Convecting Magnetic Loops and Arcades; Sep. 1996
- NIFS-449 T. Aoki,

Interpolated Differential Operator (IDO) Scheme for Solving Partial Differential Equations; Sep. 1996

- NIFS-450 D. Biskamp and T. Sato,
Partial Reconnection in the Sawtooth Collapse; Sep. 1996
- NIFS-451 J. Li, X. Gong, L. Luo, F.X. Yin, N. Noda, B. Wan, W. Xu, X. Gao, F. Yin, J.G. Jiang, Z. Wu., J.Y. Zhao, M. Wu, S. Liu and Y. Han,
Effects of High Z Probe on Plasma Behavior in HT-6M Tokamak; Sep. 1996
- NIFS-452 N. Nakajima, K. Ichiguchi, M. Okamoto and R.L. Dewar,
Ballooning Modes in Heliotrons/Torsatrons; Sep. 1996 (IAEA-CN-64/D3-6)
- NIFS-453 A. Iiyoshi,
Overview of Helical Systems; Sep. 1996 (IAEA-CN-64/O1-7)
- NIFS-454 S. Saito, Y. Nomura, K. Hirose and Y.H. Ichikawa,
Separatrix Reconnection and Periodic Orbit Annihilation in the Harper Map; Oct. 1996
- NIFS-455 K. Ichiguchi, N. Nakajima and M. Okamoto,
Topics on MHD Equilibrium and Stability in Heliotron / Torsatron; Oct. 1996
- NIFS-456 G. Kawahara, S. Kida, M. Tanaka and S. Yanase,
Wrap, Tilt and Stretch of Vorticity Lines around a Strong Straight Vortex Tube in a Simple Shear Flow; Oct. 1996
- NIFS-457 K. Itoh, S.-I. Itoh, A. Fukuyama and M. Yagi,
Turbulent Transport and Structural Transition in Confined Plasmas; Oct. 1996
- NIFS-458 A. Kageyama and T. Sato,
Generation Mechanism of a Dipole Field by a Magnetohydrodynamic Dynamo; Oct. 1996
- NIFS-459 K. Araki, J. Mizushima and S. Yanase,
The Non-axisymmetric Instability of the Wide-Gap Spherical Couette Flow; Oct. 1996
- NIFS-460 Y. Hamada, A. Fujisawa, H. Iguchi, A. Nishizawa and Y. Kawasumi,
A Tandem Parallel Plate Analyzer; Nov. 1996
- NIFS-461 Y. Hamada, A. Nishizawa, Y. Kawasumi, A. Fujisawa, K. Narihara, K. Ida, A. Ejiri, S. Ohdachi, K. Kawahata, K. Toi, K. Sato, T. Seki, H. Iguchi, K. Adachi, S. Hidekuma, S. Hirokura, K. Iwasaki, T. Ido, M. Kojima, J. Koong, R. Kumazawa, H. Kuramoto, T. Minami, I. Nomura, H. Sakakita, M. Sasao, K.N. Sato, T. Tsuzuki, J. Xu, I. Yamada and T. Watari,
Density Fluctuation in JIPP T-IIU Tokamak Plasmas Measured by a Heavy Ion Beam Probe; Nov. 1996

- NIFS-462 N. Katsuragawa, H. Hojo and A. Mase,
Simulation Study on Cross Polarization Scattering of Ultrashort-Pulse Electromagnetic Waves; Nov. 1996
- NIFS-463 V. Voitsenya, V. Konovalov, O. Motojima, K. Narihara, M. Becker and B. Schunke,
Evaluations of Different Metals for Manufacturing Mirrors of Thomson Scattering System for the LHD Divertor Plasma; Nov. 1996
- NIFS-464 M. Pereyaslavets, M. Sato, T. Shimozuma, Y. Takita, H. Idei, S. Kubo, K. Ohkubo and K. Hayashi,
Development and Simulation of RF Components for High Power Millimeter Wave Gyrotrons; Nov. 1996
- NIFS-465 V.S. Voitsenya, S. Masuzaki, O. Motojima, N. Noda and N. Ohyabu,
On the Use of CX Atom Analyzer for Study Characteristics of Ion Component in a LHD Divertor Plasma; Dec. 1996
- NIFS-466 H. Miura and S. Kida,
Identification of Tubular Vortices in Complex Flows; Dec. 1996
- NIFS-467 Y. Takeiri, Y. Oka, M. Osakabe, K. Tsumori, O. Kaneko, T. Takanashi, E. Asano, T. Kawamoto, R. Akiyama and T. Kuroda,
Suppression of Accelerated Electrons in a High-current Large Negative Ion Source; Dec. 1996
- NIFS-468 A. Sagara, Y. Hasegawa, K. Tsuzuki, N. Inoue, H. Suzuki, T. Morisaki, N. Noda, O. Motojima, S. Okamura, K. Matsuoka, R. Akiyama, K. Ida, H. Idei, K. Iwasaki, S. Kubo, T. Minami, S. Morita, K. Narihara, T. Ozaki, K. Sato, C. Takahashi, K. Tanaka, K. Toi and I. Yamada,
Real Time Boronization Experiments in CHS and Scaling for LHD; Dec. 1996
- NIFS-469 V.L. Vdovin, T. Watari and A. Fukuyama,
3D Maxwell-Vlasov Boundary Value Problem Solution in Stellarator Geometry in Ion Cyclotron Frequency Range (final report); Dec. 1996
- NIFS-470 N. Nakajima, M. Yokoyama, M. Okamoto and J. Nührenberg,
Optimization of M=2 Stellarator; Dec. 1996
- NIFS-471 A. Fujisawa, H. Iguchi, S. Lee and Y. Hamada,
Effects of Horizontal Injection Angle Displacements on Energy Measurements with Parallel Plate Energy Analyzer; Dec. 1996
- NIFS-472 R. Kanno, N. Nakajima, H. Sugama, M. Okamoto and Y. Ogawa,
Effects of Finite- β and Radial Electric Fields on Neoclassical Transport in the Large Helical Device; Jan. 1997
- NIFS-473 S. Murakami, N. Nakajima, U. Gasparino and M. Okamoto,
Simulation Study of Radial Electric Field in CHS and LHD; Jan. 1997

- NIFS-474 K. Ohkubo, S. Kubo, H. Idei, M. Sato, T. Shimozuma and Y. Takita,
Coupling of Tilting Gaussian Beam with Hybrid Mode in the Corrugated Waveguide; Jan. 1997
- NIFS-475 A. Fujisawa, H. Iguchi, S. Lee and Y. Hamada,
Consideration of Fluctuation in Secondary Beam Intensity of Heavy Ion Beam Probe Measurements; Jan. 1997
- NIFS-476 Y. Takeiri, M. Osakabe, Y. Oka, K. Tsumori, O. Kaneko, T. Takanashi, E. Asano, T. Kawamoto, R. Akiyama and T. Kuroda,
Long-pulse Operation of a Cesium-Seeded High-Current Large Negative Ion Source; Jan. 1997
- NIFS-477 H. Kuramoto, K. Toi, N. Haraki, K. Sato, J. Xu, A. Ejiri, K. Narihara, T. Seki, S. Ohdachi, K. Adati, R. Akiyama, Y. Hamada, S. Hirokura, K. Kawahata and M. Kojima,
Study of Toroidal Current Penetration during Current Ramp in JIPP T-IIU with Fast Response Zeeman Polarimeter; Jan. 7, 1997
- NIFS-478 H. Sugama and W. Horton,
Neoclassical Electron and Ion Transport in Toroidally Rotating Plasmas; Jan. 1997
- NIFS-479 V.L. Vdovin and I.V. Kamenskij,
3D Electromagnetic Theory of ICRF Multi Port Multi Loop Antenna; Jan. 1997
- NIFS-480 W.X. Wang, M. Okamoto, N. Nakajima, S. Murakami and N. Ohyabu,
Cooling Effect of Secondary Electrons in the High Temperature Divertor Operation; Feb. 1997
- NIFS-481 K. Itoh, S.-I. Itoh, H. Soltwisch and H.R. Koslowski,
Generation of Toroidal Current Sheet at Sawtooth Crash; Feb. 1997
- NIFS-482 K. Ichiguchi,
Collisionality Dependence of Mercier Stability in LHD Equilibria with Bootstrap Currents; Feb. 1997
- NIFS-483 S. Fujiwara and T. Sato,
Molecular Dynamics Simulations of Structural Formation of a Single Polymer Chain: Bond-orientational Order and Conformational Defects; Feb. 1997
- NIFS-484 T. Ohkawa,
Reduction of Turbulence by Sheared Toroidal Flow on a Flux Surface; Feb. 1997